

Montréal, 21 juin 2022.

MADAME KRISTINE TREPANIER
ABSA
9410 - 20 AVENUE N.W.
EDMONTON ALBERTA
CANADA T6N 0A4

Fabricant : CRANE INSTRUMENTATION SAMPLING INC
405 CENTURA COURT
SPARTANBURG SC
USA 29303

Numéro de dossier : 947748

Numéro(s) de dessin(s) : GO Reg CRN Scope of Registration -03312022_r1

Objet : Enregistrement des plans et devis – Confirmation de l'enregistrement

Bonjour,

Nous vous informons que votre demande d'enregistrement de plans et devis a été traitée et que cette conception a été enregistrée sous le numéro d'enregistrement canadien (NEC\CRN) suivant : **0C21718.26**.

Nous portons votre attention sur certaines exigences réglementaires concernant les installations sous pression, ainsi que des codes et normes qui y sont associés :

- Le fabricant doit maintenir un programme de contrôle de la qualité valide pour fabriquer un équipement selon ce NEC;
- Ce numéro d'enregistrement demeure valide tant et aussi longtemps que les paramètres de conception demeurent inchangés. Dans le cas d'accessoires, l'enregistrement est valide pour une durée de 10 ans à partir de la date de conception doivent alors être resoumis pour validation;
- Le fabricant doit nous transmettre une copie de l' *Déclaration de conformité du constructeur (Manufacturer's Data Report)* pour chaque appareil ou chaudière fabriqué selon ce NEC dans les 30 jours suivant la signature de cette déclaration;
- Le numéro de dessin enregistré et le numéro de révision doivent être indiqués sur la déclaration de conformité pour les équipements fabriqués selon ce NEC.

Le présent avis d'approbation ne dégage pas le fabricant de ses responsabilités quant à la conception ou à la construction des équipements ou d'accessoires fabriqués selon un NEC.

Bureau d'expertise et d'homologation en équipements sous pression

Montréal

545, boul. Crémazie Est, 7ième étage

Montréal (Québec) H2M 2V2

Téléphone : 514 873-6459

Sans frais : 1 866 262-2084

www.rbq.gouv.qc.ca

Montréal, le 21 juin 2022.

MRS. KRISTINE TREPANIER
ABSA
9410 - 20 AVENUE N.W.
EDMONTON ALBERTA
CANADA T6N 0A4

Manufacturer : CRANE INSTRUMENTATION SAMPLING INC
405 CENTURA COURT
SPARTANBURG SC
USA 29303

OUR REFERENCE : 947748

Design number : GO Reg CRN Scope of Registration -03312022_r1

Subject: Design registration confirmation

Hi,

We wish to inform you that your design registration application has been evaluated and that it was registered under the following Canadian Registration Number (CRN): **0C21718.26**.

The following is a reminder of your obligations regarding certain requirements of the regulation respecting pressure vessels, and the referenced codes and standards:

- The manufacturer must maintain a valid quality control program to manufacture equipment according to the CRN.
- The CRN remains valid as long as there are no changes to the design calculations that might affect the pressure boundary. The design registration of fittings expires 10 years after acceptance. It must, therefore, be resubmitted for validation.
- The manufacturer shall submit a copy of the *Manufacturer's Data Report* to us for each equipment manufactured according to this CRN within 30 days following the signing of this report.
- The drawing number and the revision number registered under this CRN must be indicated on the *Manufacturer's Data Report* for equipment manufactured according to the CRN.

This notice of approval does not relieve the manufacturer of their responsibilities with respect to the design or fabrication of equipment manufactured according to this CRN.

Yours sincerely,

Bureau d'expertise et d'homologation en équipements sous pression

Montréal

545, boul. Crémazie Est, 7ième étage
Montréal (Québec) H2M 2V2
Téléphone : 514 873-6459
Sans frais : 1 866 262-2084
www.rbq.gouv.qc.ca

Statutory Declaration Registration of Fittings

Building Act (B-1.1)
Regulation respecting pressure vessels (B-1.1, r. 6.1)
Boiler, pressure vessel, and pressure piping code (CSA B51)

CRANE

GO REGULATOR

This declaration must be filled out and sent to the Régie du bâtiment du Québec (RBQ) by pressure fitting manufacturers when they make an application registration for fittings.

For more information on the application registration for fittings, consult the www.rbq.gouv.qc.ca/fittings-pv.

1. Fittings to register

List the fittings included in this declaration and that you wish to register.

N°	Description	Additional information (detail, calculations or approval sheets)
1	GO REGULATOR	SCOPE OF REGISTRATION
2		
3		
4		
5		

2. Declaration of the person in charge

The person in charge is someone in a position of authority, such as a vice-president, a plant manager or a chief engineer.

2.1 Design

I, the undersigned, PAUL WRIGHT ENGINEERING SUPERVISOR,
(Name of the person in charge) (Title of the person in charge)

from CRANE INSTRUMENTATION, located at 405 CENTURA COURT, SPARTANBURG, SC 29303 USA
(Company's name) (Plant's address)

hereby declare that the above-mentioned fittings and subject to the Regulation respecting pressure installations:

comply with the requirements of the ANSI/ASME codes as to their dimensions, identification, material and purpose
or
 are not covered by the ANSI/ASME codes, but are in compliance with ASME B31.3 2020 Ed.
(Name of code or standard)


code or standard and are designed according to the best current engineering practice, as proven by the enclosed approval report.

2.2 Manufacturing quality control


I further declare that the manufacture of these fittings is controlled by a quality control program that complies with the requirements of the following code: ISO 9001: 2015, and has been verified by SAI GLOBAL.
(Name of code) (Authorized agency)

Signature of the person in charge: Paul Wright Date (yyyy-mm-dd): 2022-04-08

3. Declaration of commissioner for oaths

I certify that this declaration has been administered before me, at <u>Spartanburg SC</u> , on <u>2022-04-08</u> . (Location) (Date (yyyy-mm-dd)):	
Signature of commissioner for oaths: <u>Cymbeline L.E. Rogers</u>	Date (yyyy-mm-dd): <u>2022-04-08</u>
Stamp the seal: 	

4. Registration confirmation (for RBQ's use only)

As far as I know, this application complies with the requirements of the Act and with standard CSA B51, Part 1, section 4.2, and is accepted for registration in the class _____.	
This registration expires in ten (10) years after the date of registration indicated above, and it must be validated again after this period.	
Canadian registration number (CRN):	Registration date (yyyy-mm-dd):
	

Documents to attach

Any application registration for fittings must include these documents:

- Statutory Declaration Registration of Fittings (2 copies)
- Detailed calculations or burst test report (1 copy)
- Detailed technical drawings or catalogues (2 copies)
- Example of the manufacturer's marking (1 copy)
- Proof that a valid and approved quality control program has been implemented (1 copy)
- Form Application for design registration (1 copy)

Sending the form

This declaration is necessary to submit an application for design registration. Design registration applications must be sent by email only to enregistrementdesplans@rbq.gouv.qc.ca.

Documents must be in PDF format and in separate files.

GO Regulator Series	Main Pressure Bearing Components	Conn. Sizes	Min. Design Metal Temp. (MDMT)	Maximum Allowable Working Pressure		Design Code of Construction
				MDMT ≤ T ≤ 100°F	At Max. Temp.	
CPR1	ASTM A479 / ASME SA-479 316L SST	Various	-40°F	HS: 6250 PSI LS: 1800 PSI	HS: 6250 PSI @ 500°F LS: 1800 PSI @ 500°F	ASME B31.1 ASME B31.3
CV2	ASTM A479 / ASME SA-479 316/316L SST			HS: 5275 PSI LS: 650 PSI	HS: 5275 PSI @ 500°F LS: 650 PSI @ 500°F	
CYL20 / C2	ASTM A479 / ASME SA-479 316/316L SST			HS: 5800 PSI LS: 575 PSI	HS: 5800 PSI @ 500°F LS: 575 PSI @ 500°F	
HPR-2 / H2 (SST)	ASTM A479 / ASME SA-479 316/316L SST			HS: 5600 PSI LS: 675 PSI	HS: 5600 PSI @ 500°F LS: 675 PSI @ 500°F	
HPR-2 / H2 (MONEL)	ASTM B164 / ASME SB-164 N04405 ASTM A479 / ASME SA-479 316/316L SST			HS: 3100 PSI LS: 750 PSI	HS: 3100 PSI @ 500°F LS: 750 PSI @ 500°F	
HPR-2 / H2 (HAST C276)	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 3500 PSI LS: 650 PSI	HS: 3500 PSI @ 500°F LS: 650 PSI @ 500°F	
MR	ASTM A479 / ASME SA-479 316L SST			HS / LS: 4500 PSI	HS / LS: 4500 PSI @ 500°F	
PR1 COM1 COM2	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 4400 PSI LS: 550 PSI	HS: 4400 PSI @ 500°F LS: 550 PSI @ 500°F	
PR9	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 5000 PSI LS: 900 PSI	HS: 5000 PSI @ 500°F LS: 900 PSI @ 500°F	
PR11	ASTM B2111 - T3 ASTM B211 - T351			HS: 4650 PSI LS: 1450 PSI	HS: 4650 PSI @ 500°F LS: 1450 PSI @ 500°F	



GO Regulator Series	Main Pressure Bearing Components	Conn. Sizes	Min. Design Metal Temp. (MDMT)	Maximum Allowable Working Pressure		Design Code of Construction
				MDMT ≤ T ≤ 100°F	At Max. Temp.	
PR7 PR7LF PR7ULF	ASTM A479 / ASME SA-479 316L SST	Various	-40°F	HS: 3600 PSI LS: 500 PSI	HS: 3600 PSI @ 250°F LS: 500 PSI @ 250°F	ASME B31.1 ASME B31.3
PR59	ASTM A479 / ASME SA-479 316/316L SST			HS / LS: 4000 PSI	HS / LS: 4000 PSI @ 175°F	
BP3	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 4400 PSI LS: 550 PSI	HS: 4400 PSI @ 500°F LS: 550 PSI @ 500°F	
PR5	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 4400 PSI LS: 550 PSI	HS: 4400 PSI @ 500°F LS: 550 PSI @ 500°F	
CYL21 / C1	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 4400 PSI LS: 550 PSI	HS: 4400 PSI @ 500°F LS: 550 PSI @ 500°F	
BP8 BP8LF	ASTM A479 / ASME SA-479 316L SST			HS: 3600 PSI LS: 500 PSI	HS: 3600 PSI @ 250°F LS: 500 PSI @ 250°F	
SBPR	ASTM A479 / ASME SA-479 316L SST			HS: 3600 PSI LS: 500 PSI	HS: 3600 PSI @ 250°F LS: 500 PSI @ 250°F	
SPR	ASTM A479 / ASME SA-479 316L SST			HS: 3600 PSI LS: 500 PSI	HS: 3600 PSI @ 250°F LS: 500 PSI @ 250°F	
HB2 (316 SST)	ASTM A479 / ASME SA-479 316/316L SST			HS: 5600 PSI LS: 675 PSI	HS: 5600 PSI @ 500°F LS: 675 PSI @ 500°F	
HB2 (MONEL)	ASTM B164 / ASME SB-164 N04405 ASTM A479 / ASME SA-479 316/316L SST			HS: 3100 PSI LS: 750 PSI	HS: 3100 PSI @ 500°F LS: 750 PSI @ 500°F	
HB2 (HAST C276)	ASTM B574 / ASME SB-574 N10276 ASTM A479 / ASME SA-479 316/316L SST			HS: 3500 PSI LS: 650 PSI	HS: 3500 PSI @ 500°F LS: 650 PSI @ 500°F	